

Programmable 3 Channel High-Performance Power Supply HMP4030

1st Quarter
2009



HMP4030



EasyArb functionality for simple voltage- and current characteristics



Silicone test cable HZ10



Ethernet/USB-interface HO730 for industrial use (Option)



- 3 x 0...32V/0...10A, 384W max.
- 384W output power realized by intelligent power management
- Low residual ripple: <150 µV_{rms} due to linear post regulators
- High setting- and read-back resolution of 1mV/0.2mA
- Keypad for direct parameter entry
- Galvanically isolated, earth-free output channels
- Advanced parallel- and serial operation via V/I tracking
- EasyArb function for free definable V/I characteristics
- FuseLink: individual channel combination of electronic fuses
- Free adjustable overvoltage protection (OVP) for all outputs
- All parameters clearly displayed via LCD/glowing buttons
- Rear connectors for all channels including sense
- USB/RS-232 Interface, optional Ethernet/USB or IEEE-488

Programmable 2 Channel High Performance Power Supply HMP2020**Programmable 3 Channel High Performance Power Supply HMP2030****Programmable 3 Channel High Performance Power Supply HMP4030**

All data valid at 23 °C after 30 minute warm-up

Outputs

Advanced parallel and series operation: simultaneously switch on/off of active channels via 'Output' button, common voltage- and current control using tracking mode (individual channel linking), individual mapping of channels which shall be affected by FuseLink overcurrent protection (switch-off), all channels galvanically isolated and independent from protective earth

HMP2020 1 x 0...32V/0...10A 0...5.5V/0...5A

HMP2030 2 x 0...32V/0...5A 0...5.5V/0...5A

HMP4030 3 x 0...32V/0...10A

Output terminals: 4mm safety sockets frontside
Screw-type terminal rear side
(4 units per channel)

Output power:

HMP2020/HMP2030 188W max.

HMP4030 384W max.

Compensation of lead resistances (Sense):

1V

Overvoltage / overcurrent protection (OVP/OCP):

Adjustable for each channel

Electronic fuse: Adjustable for each channel, combinable via FuseLink

Response time: <10ms**32V channels****Output values:**

HMP2020 1 x 0...32V/0...10A, (5A at 32V)

HMP2030 2 x 0...32V/0...5A, (2.5A at 32V)

HMP4030 3 x 0...32V/0...10A, (5A at 32V)

Resolution:

Voltage 1mV

Current HMP2030 <1A: 0.1mA; ≥1A: 1mA

Current HMP2020/4030 <1A: 0.2mA; ≥1A: 1mA

Setting accuracy:

Voltage <0.05% + 5mV (typ. ±2mV)

Current HMP2030 <0.1% + 5mA (typ. ±0.5mA at I < 500mA)

Current HMP2020/4030 <0.1% + 5mA (typ. ±1mA at I < 500mA)

Measurement accuracy:

Voltage <0.05% + 2mV

Current HMP2030 <500mA: <0.05% + 0.5mA, typ. ±0.2mA

Current HMP2030 ≥ 500mA: <0.05% + 2mA, typ. ±1mA

Current HMP2020/4030 <500mA: <0.05% + 0.5mA, typ. ±0.5mA

Current HMP2020/4030 ≥ 500mA: <0.05% + 2mA, typ. ±2mA

Residual ripple (3Hz...100kHz):Voltage <150µV_{rms}Current <1mA_{rms}**Stabilisation at load change (10%...90%):**

Voltage <0.01% + 2mV

Current <0.01% + 250µA

Stabilisation at line voltage variation (±10%):

Voltage <0.01% + 2mV

Current <0.01% + 250µA

Entire load regulation:(at 10%...90% load peak, balance time to match within 10mV U_{nom}) <50µs**Residual ripple (3Hz...100kHz):**Voltage <150µV_{rms}Current <1mA_{rms}**Stabilisation at load change (10%...90%):**

Voltage <0.01% + 2mV

Current <0.01% + 250µA

Stabilisation at line voltage variation (±10%):

Voltage <0.01% + 2mV

Current <0.01% + 250µA

Entire load regulation:(at 10%...90% load peak, balance time to match within 10mV U_{nom}) <50µs**Arbitrary Function easyARB [32V and 5V channels]****Parameters of points:** Voltage, current, time**Number of points:** 128**Dwell time:** 10ms ... 100s**Repetition rate:** Continuously or burst mode with 1...255 changes**Trigger:** Manually via keyboard or via Interface**Maximum ratings****Reverse voltage:** 33V max.**Incorrectly polarized voltage:** 0.4V max.**Max. permitted current in case of reverse voltage:** 5A max.**Voltage to earth:** 150V max.**Miscellaneous****Temperature coefficient / °C:**

Voltage 0.01% + 2mV

Current 0.02% + 3mA

Display:

HMP2020/HMP2030 240 x 64 Pixel LCD (full graphical)

HMP4030 240 x 120 Pixel LCD (full graphical)

Memory: Non volatile memory for 3 Arbitrary functions and 10 device settings**Interface:** Dual-Interface USB/RS-232 (H0720)**Process time:** <50ms**Protection class:** Safety class I (EN61010-1)**Power supply:** 115/230V ± 10%; 50/60Hz, CAT II**Mains fuse:** Microfuse 5 x 20mm slow blow

HMP2020/HMP2030 115V: 2 x 6A

230V: 2 x 3.15A

HMP4030 115V: 2 x 10A

230V: 2 x 5A

Power consumption:

HMP2020/HMP2030 350VA max.

HMP4030 550VA max.

Operating temperature: +5°C...+40°C**Storage temperature:** -20°C...+70°C**Max. rel. humidity:** 5%...80% (non condensing)**Dimensions (W x H x D):**

HMP2020/HMP2030 285 x 75 x 365mm

HMP4030 285 x 125 x 365mm

Weight:

HMP2020/HMP2030 8.5kg

HMP4030 approx. 10kg

5.5V channel**Output values:**

HMP2020/HMP2030 1 x 0...5.5V/0...5A

Resolution:

Voltage 1mV

Current <1A: 0.1mA; ≥1A: 1mA

Setting accuracy:

Voltage <0.05% + 5mV (typ. ±2mV)

Current <0.1% + 5mA (typ. ±0.5mA at I < 500mA)

Measurement accuracy:

Voltage <0.05% + 2mV

Current <500mA: <0.05% + 0.5mA; typ. ±0.2mA

Current ≥ 500mA: <0.05% + 2mA, typ. ±1mA

Accessories supplied: Line cord, Operating manual, Dual-Interface USB/RS-232 (H0720), CD**Optional accessories:**

H0730 Dual-Interface Ethernet/USB

H0740 Interface IEEE-488 (GPIB), galvanically isolated

HZ10S 5 x silicone test lead (measurement connection in black)

HZ10R 5 x silicone test lead (measurement connection in red)

HZ42 2RU 19" Rackmount Kit (HMP2020, HMP2030)

HZ43 3RU 19" Rackmount Kit (HMP4030)

www.hameg.com